

LISTING OF THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) For use in an ultra wideband (UWB) communication system, apparatus capable of directing selected UWB pulses to and from selected multiple users, the apparatus comprising:

a wideband antenna structure having multiple arrays, each array having multiple antenna elements; and

means for separating UWB pulses into individual user streams of pulses by assigning to each user a unique combination of a UWB frequency and an antenna array, such that the UWB pulses transmitted to or from particular users are all uniquely identifiable and that a given one of the particular users may at least one of receive and transmit UWB pulses at the same time as others of the particular users without significant interference, and for applying each user stream to the antenna structure ~~in such a way as to generate individual user beams containing only pulses intended for those respective users.~~

2. (Original) Apparatus as defined in claim 1, wherein:

the means for separating UWB pulses into individual user streams comprises means for assigning to each user a particular allocation of UWB time slots.

3. (Original) Apparatus as defined in claim 1, wherein:

the means for separating UWB pulses into individual user streams comprises means for applying each user stream to a different segment of the antenna.

4. (Cancelled)

5. (Currently Amended) Apparatus as defined in claim [[4]] 1, wherein the means for separating UWB pulses into user streams comprises:

a plurality of beam forming networks, each associated with a separate one of the multiple antenna arrays, and each comprising a plurality of variable time delay circuits, wherein the time delay circuits interpose different sets of selected time delays for UWB pulses applied to the successive array elements, to direct different pulses along beam paths to respective users; and

means for generating beam steering signals to the beam forming networks, to switch the beam forming networks to effect beam steering toward selected users served by each antenna array.

6. (Currently Amended) Apparatus as defined in claim 5, wherein:

each beam forming network is switchable to direct beams to a plurality (m) of users associated with each antenna array;

the antenna structure has n arrays, for a total of mn users;

UWB pulses for each of the mn users have a ~~carrier~~ frequency selected from a plurality of available frequencies; and

the plurality of available frequencies are reused in a spatial sequence such that the beam associated with any user is spatially separated from other user beams using the same frequency.

7. (Currently Amended) A method for transmitting ultra wideband (UWB) pulses to selected multiple users, comprising the steps of:

separating UWB pulses by individual user based on assigning to each user a unique combination of a UWB frequency and an antenna array, such that the transmitted and received UWB pulses are all uniquely identifiable to particular users and that a given one of the particular users may at least one of receive and transmit UWB pulses at the same time as others of the particular users without significant interference; and

applying the UWB pulses to a wideband antenna structure having multiple arrays of multiple antenna elements.

8. (Original) A method as defined in claim 7, wherein:

the step of separating UWB pulses comprises assigning each user a particular allocation of time slots in a stream of UWB pulses.

9. (Original) A method as defined in claim 7, wherein:

the step of separating UWB pulses comprises applying each user's pulses to a different segment of the antenna structure.

10. (Cancelled)

11. (Currently Amended) A method as defined in claim ~~[[10]]~~ 7, wherein:

the step of separating UWB pulses comprises forming beams in a plurality of beam forming networks, each associated with a separate one of the multiple antenna arrays, wherein the step of forming beams includes interposing different sets of selected time delays for UWB pulses applied to the successive array elements, to direct different pulses along beam paths to respective users; and

the method further comprises generating beam steering signals to the beam forming networks, and thereby switching the beam forming networks to effect beam steering toward selected users served by each antenna array.

12. (Currently Amended) A method as defined in claim 11, wherein:

the step of switching the beam forming network functions to direct beams to a plurality (m) of users associated with each antenna array;

the antenna structure has n arrays, for a total of mn users; and

the method further comprises selecting, for each of the mn users, a UWB ~~earrier~~ frequency from a plurality of available frequencies, and reusing the plurality of available

frequencies in a spatial sequence such that the beam associated with any user is spatially separated from other user beams using the same frequency.